

## ECORETARD NC

### Main Description:

Lubricant for Printing Paste.

### Chemical Structure:

Organic salts and ethoxylated esters.

### Technical Specification:

Appearance at 20-25°C

Colourless Liquid

pH Value at 20-25°C

Approx. 7.0-9.0

### Properties:

- Soluble in cold water at all proportions.
- It can be used indistinctly in all kinds of textile printing pastes.
- Does not stiffen the printed fabric, but helps reach a smooth handle.
- It provides great stability to the emulsion, without producing exaggerated drops of viscosity when diluting it. It speeds up the subsequent drying, giving a better thermo-fixation.

### Application:

It is added directly to the printing formulation, without being previously diluted, at an approximate dosage of 5 to 15 g/kg of paste.

### Storage:

The product is stable for 12 months, whenever kept in the original containers, well-closed and protected from weather inclemencies at a maximum temperature of 35 °C.



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at your service for further information and advice. Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding with regard to possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods which are beyond our control.