

# ECOMIN GREEN HF

**Stable aqueous dispersion of green pigment with high fastness performance and color yield.**



**Physical Appearance**  
Green Liquid



**pH**  
7.0-8.0



**Color Change**  
 $\Delta E < 1\%$



**Solubility**  
Soluble in water



**Odor**  
Odorless



**Storage**  
12 months, 25-35 °C.



**Health & Safety**  
SDS available upon request.



## Fastness Properties:

Fastness (at 3%)	Value
Lightfastness (ISO 105-B02)	<b>7-8</b>
Washing Fastness (ISO 105-C06)	<b>5</b>
Rubbing Fastness (ISO 105-X12)	<b>Dry: 5, Wet: 4</b>
Heat Stability (ISO 105-P01)	<b>4-5</b>
Dry Cleaning (ISO 105-D01)	<b>4-5</b>
PVC Coating (ISO 105-X10)	<b>4-5</b>
Discharge (80g/ kg Decroline)	<b>5</b>



## Features:

- **ECOMIN GREEN HF** is a very fine dispersion.
- **ECOMIN GREEN HF** is a bright and clear pigment
- **ECOMIN GREEN HF** has excellent fastness to light and washing as compared to traditional pigments.



## Application:

- **ECOMIN GREEN HF** can be used in all water-based pastes, where high fastness performance is required.
- When used above 5% in printing pastes, adding 2-5% **ECOFIX PF** is recommended.



[www.printexchemicals.com](http://www.printexchemicals.com)



[info@printexchemicals.com](mailto:info@printexchemicals.com)



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at your service for further information and advice.