

Phthalate & PVC free printing paste used to achieve an elastic, soft touching and Silver effect in textile printing.



Chemical NaturePhthalate & PVC Free, Oil Base



Ionic NatureNon-Ionic



pH ≈ 7 ± 0.5



Physical Appearance Silver Paste



Fabric TypeCotton, PES, CO/PES blend fabric



Squeegee Shore: Medium 65



Mesh Count: 43-120 T



Health & Safety SDS available upon request



Date of Compilation: MAR-2024



Product Feature

- Provides a clear silver print.
- It is ready to use paste and does not require any preparation before printing.
- Provides a very good wash fastness, maintaining print quality even after multiple washes and wears.
- Ensures strong bonding with the fabric, preventing peeling or cracking.
- Provides an even and consistent print surface for professional results.
- Exhibits superior elasticity, ensuring flexibility and durability in printed textiles.



Application

- Before use, please stir this product well. Do not use any additives that are not advised.
- If necessary, to reduce viscosity adding 1-3% **Ecopure Thinner** is recommended.
- Once printed, crosslink at 150° -160°C (3-2 Min).
- After use, the screen should be cleaned with the **Ecopure Thinner**.
- Allow 24 hrs. after heat curing before evaluation of the final prints.



Storage

 Stable for 12 months, whenever kept in the original containers at 25-35 °C



www.printexchemicals.com



info@printexchemicals.com



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.

Page: 1 of 1 Version: 1