

Website: www.printexchemicals.com

Email: info@printexchemicals.pk

ECOSILC SILVER

Main Description:

Silver effect silicone.

Properties:

- High elongation
- gloss effect
- Excellent wash durability
- Easily pigmented
- Fast cure
- Cures at low temperatures
- Soft hand feeling.

Application:

- 1. It can be used for silver effect printing.
- 2. It can be mixed with pigment to match out the colorful silicone for color printing.

Usage:

Printing

Mix with 2 to 4% Ecosilc Catalyst & then print.

Crosslink at 150° -160 °C (3-2 Min).

Cleaning

Clean the screen with Ecoslic Thinner after printing.

Storage:

The product is stable for 12 months, when kept in the original containers, well-closed and protected from weather inclemencies at a maximum temperature of 35 $^{\circ}$ C.



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at your service for further information and advice. Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding with regard to possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods which are beyond our control.

ECOSILC SILVERPage 1 of 1Date of Compilation: AUG 2022Date of Revision: MAR 2024Revision: 1