


ECOPRINT AUTOCRACK CLEAR

Ready-to-use white lacquer paste which, once printed and dried gives earthquake effect.



Chemical Nature
Acrylic Emulsion.



Ionic Nature
Anionic



Viscosity
46000-50000 m-Pas
(NDJ-5S), Sp L4 at
12rpm at 20-25°C



pH
8-9



Physical Appearance
Clear Transparent Paste



Fabric Type
Cotton, PES, CO/PES
blend fabric



Squeegee
Shore: 65-75



Mesh
Count: 43-62 T



Health & Safety
SDS available upon
request



Product Feature

- ECOPRINT AUTOCRACK CLEAR creates a unique, cracked appearance in bright colored ways resembling the aftermath of an earthquake, adding a distinctive texture to the print
- It has very good fastness to wet washing and dry and wet rubbing.
- It has a good coverage.
- It has been formulated with environmentally friendly ingredients, making it a sustainable choice.



Application

- The following steps are recommended
 - 1st & 2nd coat: ECOPRINT AUTOCRACK BASE
 - Dry
 - 3rd, 4th & 5th coat: ECOPRINT AUTOCRACK CLEAR
 - Dry
 - Crosslink at 150°C (4 Min).
- Depending on the fabrics where it is applied it begins to auto-break with heat, nevertheless, we recommend carrying out a wet washing with rubbing to achieve the best results.



Storage

- Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.