ECOPRINT CLEAR 702

Environment Friendly Water Based Very Soft & Elastic Clear Printing Paste.



Chemical Nature Acrylic Emulsion.



Ionic Nature Anionic



Viscosity 48000-51000 m-Pas (NDJ-5S), Sp L4 at 12rpm at 20-25°C



pH 8-9



Physical Appearance Clear Transparent Paste



Fabric Type Cotton, PES, CO/PES blend fabric



Squeegee Shore: 65-75



Mesh Count: 43-62 ⊤



Health & Safety SDS available upon request





- It has a high color yield.
- It has good wash fastness and is soft to the touch.
- It has high elasticity.
- It is easy to use, suitable for hand printing.
- It is suitable to the environmental standards.

Application

- For the best result, please print at a moisture condition of 50-80% and note the impact of temperature on operability.
- Make sure the fabric is not the sublimed fabric.
 If yes, use anti-sublimation base ink first.
- It can be colored with 30-50 g/kg of ECOMIN pigment range.
- Once printed, crosslink at 150^o -160 ^oC (3-2 Min).

Storage

 Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com

Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.

Date of Compilation: AUG-2023