


ECOPRINT COPPER

Ready to use non-metallic base for brilliant **Copper effect**



Chemical Nature
Acrylic Emulsion.



Ionic Nature
Anionic



Viscosity
40000-45000 m-Pas
(NDJ-5S), Sp L4 at
12rpm at 20-25°C



pH
8-9



Physical Appearance
Copper Paste



Fabric Type
Cotton, PES, CO/PES
blend fabric



Squeegee
Shore: Medium 65



Mesh
Count: 32-54 T



Health & Safety
SDS available upon
request



Product Feature

- It is pre-formulated and easy to apply, saving time and effort in preparation.
- It produces a stunning, high-quality copper effect without the use of metallic particles.
- It gives an elastic and soft touching effect.
- It ensures a uniform and consistent copper effect across different printing applications.
- It maintains brilliance and stability over time, preventing fading or discoloration.
- It has been formulated with environmentally friendly ingredients, making it a sustainable choice.



Application

- For the best result, please print at a moisture condition of 50-80% and note the impact of temperature on operability.
- Make sure the fabric is not the sublimed fabric. If yes, use anti-sublimation base ink first.
- Once printed, crosslink at 150^o -160 °C (3-2 Min).



Storage

- Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.