


# ECOPRINT CRACKLE CLEAR

**Ready-to-use lacquer paste for pigmentation which, once printed and dried gives earthquake effect.**



**Chemical Nature**  
Acrylic Emulsion.



**Ionic Nature**  
Anionic



**Viscosity**  
46000-50000 m-Pas  
(NDJ-5S), Sp L4 at  
12rpm at 20-25°C



**pH**  
8-9



**Physical Appearance**  
Clear Transparent Paste



**Fabric Type**  
Cotton, PES, CO/PES  
blend fabric



**Squeegee**  
**Shore:** 65-75



**Mesh**  
**Count:** 43-62 T



**Health & Safety**  
SDS available upon  
request



## Product Feature

- ECOPRINT CRACKLE CLEAR creates a unique, cracked appearance resembling the aftermath of an earthquake, adding a distinctive texture to surfaces.
- It has very good fastness to wet washing and dry and wet rubbing.
- It has a good color yield.
- It has been formulated with environmentally friendly ingredients, making it a sustainable choice.



## Application

- To achieve the best result, it is recommended to carry out a double printing.
- Depending on the fabrics where it is applied it begins to break with a simple abrasion, nevertheless, we recommend carrying out a wet washing with rubbing to achieve the best results.
- It can be colored with 30-50 g/kg of ECOMIN range.
- Once printed, crosslink at 150° -160 °C (3-2 Min).



## Storage

- Stable for 12 months, whenever kept in the original containers at 25-35 °C.



[www.printexchemicals.com](http://www.printexchemicals.com)



[info@printexchemicals.com](mailto:info@printexchemicals.com)



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.