ECOPRINT FLOCK ST

Binder adhesive for producing a soft flock effect

Chemical Nature Acrylic Emulsion.



lonic Nature Anionic



Viscosity 47000-50000 m-Pas (NDJ-5S), Sp L4 at 12rpm at 20-25°C



pH 8-9



Physical Appearance Clear Paste



Fabric Type Cotton, PES, CO/PES blend fabric



Squeegee Shore: Medium 65



Mesh Count: 32-54 T



Health & Safety SDS available upon request



Product Feature

- ECOPRINT FLOCK ST is a ready-made thermoadhesive paste developed for T-shirt printing.
- Excellent fixation on all kinds of items.
- Specially designed for textile flocking.
- Very soft handle.
- High fastness to aqueous washings..

Application

- To achieve the best results, is recommended a medium doctor pressure so that ECOPRINT FLOCK ST could remain more superficial on the fabric and the fastness of the flock could be optimum.
- ECOPRINT FLOCK ST is printed, then it is essential to start flocking without any delay.
- The fabric that the flocking binder is applied should be placed over a metal plate and the flocking operation should be done by a wellground system flocking machine.
- We obtain the best results curing 3 Min at 170°C

Storage

• Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com

Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.

Date of Compilation: AUG-2022