


ECOPRINT MATT COATING

Ready to use base to get matt effect



Chemical Nature
Acrylic Emulsion.



Ionic Nature
Anionic



Viscosity
47000-50000 m-Pas
(NDJ-5S), Sp L4 at
12rpm at 20-25°C



pH
8-9



Physical Appearance
White Paste



Fabric Type
Cotton, PES, CO/PES
blend fabric



Squeegee
Shore: Medium 65



Mesh
Count: 32-54 T



Health & Safety
SDS available upon
request



Product Feature

- It forms a smooth surface after printing and a very good matt effect.
- It has very good adhesion with ECOPRINT Range and good washing fastness.
- It has a very good transparency and color is not prone to white after stretching.
- It has good dry and wet fastness properties.
- It is suitable for digital cover paste and elliptical printing machine operation.



Application

- For the best result, please print at a moisture condition of 50-80% and note the impact of temperature on operability.
- Make sure the fabric is not the sublimed fabric. If yes, use anti-sublimation base ink first.
- It is applied as a coating in a single stroke over the printed area to get the desired effect.
- Once printed, crosslink at 150^o -160 °C (3-2 Min).



Storage

- Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.