ECOPRINT SUPER SOFT WHITE EL

Machine Printable White in aqueous basis with excellent covering power having extra Softness and high Elasticity.



Chemical Nature Acrylic Emulsion.



Ionic Nature Anionic



Viscosity 46000-51000 m-Pas (NDJ-5S), Sp L4 at 12rpm at 20-25°C



pH 8-9



Physical Appearance White Paste



Fabric TypeCotton, PES, CO/PES blend fabric



Squeegee Shore: 65-75



Mesh Count: 43-62 T



Health & Safety SDS available upon request



Product Feature

- ECOPRINT SUPER SOFT WHITE EL features excellent covering power and high elasticity, making it ideal for use on elastic and stretchable fabrics without cracking or peeling.
- It maintains a super soft hand feel, ensuring comfort and wearability without compromising the print quality.
- It has high fastness to aqueous washing.
- It has been formulated with environmentally friendly ingredients, making it a sustainable choice.
- It is safe for use in various textile applications, including those that come into contact with skin.



Application

- It is developed for positional and T-shirt printing.
- For the best result, please print at a moisture condition of 50-80% and note the impact of temperature on operability.
- Make sure the fabric is not the sublimed fabric. If yes, use anti-sublimation base ink first.
- Once printed, crosslink at 150° -160 °C (3-2 Min).



Storage

 Stable for 12 months, whenever kept in the original containers at 25-35 °C.



Date of Compilation: MAR-2024



www.printexchemicals.com



info@printexchemicals.com



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.

Page: 1 of 1 Version: 1