


ECOPRINT WHITE 5000

Ready to use White paste with fine particle size. Especially for rotary printing machines.



Chemical Nature
Acrylic Emulsion.



Ionic Nature
Anionic



Viscosity
46000-50000 m-Pas
(NDJ-5S), Sp L4 at
12rpm at 20-25°C



pH
8-9



Physical Appearance
White Paste



Fabric Type
Cotton, PES, CO/PES
blend fabric



Squeegee
Shore: 65-75



Mesh
Count: 43-54 T



Health & Safety
SDS available upon
request



Product Feature

- It is suitable for application in flat and rotary printing machines.
- ECOPRINT WHITE 5000 has a high covering power.
- Indicated for producing whites on dyed fabric to rich tones.
- It is suitable to environmental standards.



Application

- For the best result, please print at moisture condition of 50-80% and note the impact of temperature to operability.
- Once printed, crosslink at 150° -160 °C (4-3 Min).
- On the formulations of discharge printing, the grade of white can be improved by the addition of 100 - 150 g/kg S-5 **ECOPRINT WHITE 5000**.



Storage

- Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.