


ECOPRINT WHITE 702

Environment-Friendly Water Based Very Soft & Elastic White Printing Paste.



Chemical Nature
Acrylic Emulsion.



Ionic Nature
Anionic



Viscosity
47000-50000 m-Pas
(NDJ-5S), Sp L4 at
12rpm at 20-25°C



pH
8-9



Physical Appearance
White Paste



Fabric Type
Cotton, PES, CO/PES
blend fabric



Squeegee
Shore: Medium 65



Mesh
Count: 43-62 T



Health & Safety
SDS available upon
request



Product Feature

- It has high covering Power and is suitable for table and Machine printing.
- It has good wash fastness and is soft to the touch.
- It has high elasticity and high whiteness.
- It is suitable to environmental standards.



Application

- For the best result, please print at a moisture condition of 50-80% and note the impact of temperature on operability.
- Make sure the fabric is not the sublimed fabric. If yes, use anti-sublimation base ink first.
- Once printed, crosslink at 150° -160 °C (3-2 Min).



Storage

- Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.