ECOPRINT WHITE ES-100

Machine Printable White in aqueous basis with excellent covering power having Soft feel and Elasticity.

Chemical Nature Acrylic Emulsion.



Ionic Nature Anionic

Viscosity



48000-51000 m-Pas (NDJ-5S), Sp L4 at 12rpm at 20-25ºC



pH 8-9



Physical Appearance White Paste



Fabric Type Cotton, PES, CO/PES blend fabric



Squeegee Shore: 65-75



Mesh Count: 43-62 T



Health & Safety SDS available upon request



Product Feature

- It has excellent covering power and a soft handle.
- It has high elasticity
- It has high fastness to aqueous washing.
- It is especially recommended for T-shirt printing.
- It is suitable to environmental standards.

Application

- It is developed for positional printing.
- For the best result, please print at a moisture condition of 50-80% and note the impact of temperature on operability.
- Make sure the fabric is not the sublimed fabric. If yes, use anti-sublimation base ink first.
- Once printed, crosslink at 150° -160 °C (3-2 Min).

Storage

 Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com

Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.