


ECOPRINT WHITE NE

Ready to print White paste with very soft and imitation to discharge effect on dark grounds, with flatbed and rotary machines.



Chemical Nature
Acrylic Emulsion.



Ionic Nature
Anionic



Viscosity
45000-50000 m-Pas
(NDJ-5S), Sp L4 at
12rpm at 20-25°C



pH
8-9



Physical Appearance
White Paste



Fabric Type
Cotton, PES, CO/PES
blend fabric



Squeegee
Shore: 65-75



Mesh
Count: 43-120 T



Health & Safety
SDS available upon
request



Product Feature

- It has a high covering power and very soft handle.
- Due to its rheology, it is suitable to print in rotary machines.
- It has very good run-ability properties that allows to print many colors.
- It is suitable to the environmental standards.



Application

- **ECOPRINT WHITE NE** is developed for rotary and flat-bed printing.
- It can be used with any ratio of standard emulsions when the concentration of binder guarantees that there are not losses of fastness and covering is enough to the printing.
- Once printed, crosslink at 150^o -160 °C (4-3 Min).



Storage

- Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.