

Environment Friendly Water Based Soft & Elastic White Printing Paste.



Chemical Nature Acrylic Emulsion.



Ionic Nature Anionic



Viscosity 48000-50000 m-Pas

48000-50000 m-Pa (NDJ-5S), Sp L4 at 12rpm at 20-25°C



pH 8-9



Physical AppearanceWhite Paste



Fabric TypeCotton, PES, CO/PES blend fabric



Squeegee Shore: 65-75



Mesh

Count: 43-62 T



Health & Safety SDS available upon request



Date of Compilation: MAR-2024



Product Feature

- It has a high covering power and whiteness.
- It has good wash fastness and is soft to the touch.
- It has high elasticity.
- It is easy to use and suitable for hand printing.
- It is suitable to the environmental standards.



Application

- For the best result, please print at a moisture condition of 50-80% and note the impact of temperature on operability.
- Make sure the fabric is not the sublimed fabric.
 If yes, use anti-sublimation base ink first.
- Once printed, crosslink at 150° -160°C (3-2 Min).



Storage

 Stable for 12 months, whenever kept in the original containers at 25-35 °C.



www.printexchemicals.com



info@printexchemicals.com



Information concerning the safety regulations can be taken from the Material Safety Data Sheet of this product. We reserve the right to modify the product and technical leaflet. Our department for applied technique is always at the service for further information and advice.

Page: 1 of 1 Version: 1